



常州君毅地板有限公司
CHANGZHOU JUNYI ACCESS FLOOR CO., LTD

26 HENGSHANQIAO TOWN, Changzhou Jiangsu, China

Tel:0086-519-89889352; Fax:86-519-88605659 E- mail: admin@jyaccessfloor.com;

Product data sheet	Weiss Ca Sulphate 32-34mm	60032C34F
		<p>1 Panel</p> <p>2 Pedestal</p> <p>3 Stringer</p> <p>4 Air flow</p> <p>5 Panel</p> <p>6 Screws Gaskets</p>
Panel information		
Dimensions	600x600x34mm	
Thickness of core:	32mm	
Thickness of steel:	0.40mm	
Core material:	1500 kg per CBM Gypsum	
Finish material:	Galvanized steel sheet	
Finish:	1.0mm HPL with R: 10°0hm-10°0hm	
Panel weight:	19.5 kg Per Pc	
System weight	≤ 65kg Per m ²	
Load performance		
Concentrated load	≤2.0mm deflection 6,000 N	≤2.5mm deflection 7,500 N
Ultimate load	≥ 20,000 N	
Distributed load	24,000 N/m ²	
Pedestal:	10μm(T), Galvanized steel zinc	D: ≥90mm
Tube/base:	Ø30mm #2mm(T)/125mmx125mmx3(T)	
Stringer:	U Stringer Galvanized steel	≥0.6mm(T)
Remarks:		
Fire protection		
Standard: CSN EN 13501-2 _A1:2010 art 7.3.4		Result:Non-combutible
Applications		
Data center		